	Comfort Ventilation System CVS® robusto A with standard wall plug power supply, 12V/1A (1,5m cable, phone jack 5,5/2,5mm, positive pole inside, short- circuit-proof), 2 pipes (48 cm) with 4 gaskets, 2 external blinds, 4 plugs + screws, 2 filter G3 on WT, manual, hole pattern 1:1 of carton	284,00	337,96
	Comfort Ventilation System CVS® robusto B (f. restrooms), with standard wall plug power supply, 12V/1A (1,5m cable, phone jack 5,5/2,5mm, positive pole inside, short-circuit-proof), 2 pipes (48 cm) with 4 gaskets, 2 external blinds, 4 plugs + screws, 2 filter G3 on WT, manual, hole pattern 1:1 of carton	290,00	345,10
CVS samewall	Comfort Ventilation System CVS®ammerwind® with standard wall plug power supply, 12V/1A (1,5m cable, phone jack 5,5/2,5mm, positive pole inside, short- circuit-proof), variable air stream, 6-20 m³/h, several options, very quiet 2 pipes (48 cm) with 4 gaskets, 2 external blinds, 4 plugs + screws, 2 filter G3 on WT, manual, hole pattern 1:1 of carton	325,-	386,75
	Working Hour Counter (elmech)	35.00	41,65
	Timerunit for easy slumber-/or bath-pusher- Function (up fm 9/13)	38,00	45,22
	Automatic frost protection. (uP-based, sensors, stepper motor) (from 2/14)	65,00	77,35
	Special shutter to prevent icicles 1/14	9,50	

	Heat-exchanger spare part, fits into all CVS	99,50	
15/12/2009	External cover with and w/o dropper	9,50	
	Fanmotor 8412NG for CVSrobustoA and CVSammerwind	13,50	
	Fanmotor 8412NGMLE for CVSrobustoB	15,50	
	Comfort Ventilation System CVS® jumbo (f. open plan offices, restaurants, gyms, training rooms, class rooms etc) without accessories, regulation separately parallel for up to 5 apparatus see below	722,-	859,18
	Unique control unit for the CVSjumbo. (included when single unit)	55,00	
	Accumulative control unit for 2-5 CVSjumbo's. with Central-NT	204,-	242,76

Umwelt schonendes Netzteil EuP Energieeinsparung Stand by Modus 12W 12V 93-815-01070	Normative plug power supply (1,5m cable, phone jack 5,5/2,5mm, positive pole inside, short-circuit-proof), contained at the delivery of the CVSrobusto	9,45	11,25
	Set of 2 Exterior Shutters for KGpipes DN100, incl. Water dropper, dense rings	33,00	39,17

The following components are accessories:

In the case of an order of an alternative power supply you will obtain this one au lieu of the standard power supply, which will be delivered with the CVS and we will credit you 9,45 € (net) for each ordered CVS!

Alternative power supply: Plug power supply 12V/1A clocked (87 % degree of efficiency) (1,6 m cable, jack 5,5/2,5mm, positive pole inside) Colour: anthracite	19,95	23,74
Cable extension jack 5,5/2,5mm, 4m length	6,10	7,26
Alternative power supply: Floating power supply 12V/1A clocked, suitable for each standard in-wall tin, can be installed behind the base plate of the CVS mid-symmetric to the below wall opening. Short lines enclosed for connection to screw-type terminals.	20,95	24,93

LA MARINE DOCUMENTS OF THE PARTY OF THE PART	Central power supply (12V/6A) clocked for up to 6 CVSmini, or 12 CVSrobustoA, or18 CVSrobustoB Alternatively it is possible to deliver a Nt for top hat rail mounting, same price	49,85	59,32
Verlängerungs- 6-kant Schaft Mehrzweck- Lochsäge 63mm Zentrierstein- bohrer 8mm	HM-drill bit for socket outlets 65mm Dm with 300 mm extension flagpole s. alternative drilling method under >>Info	59,00	70,21
Tigerials Principing Definition for Other States Consider and Definition and De	Pipe accommodator, clamping into the drilling machine with distance ring and reserve grinding discs	15,00	17,85
On Mode	Infrared Thermometer -33 to 210 ° C After just 0.5 seconds measuring time, the display shows the temperature of a surface to be measured without contact between - 33 and + 210 ° C reliably! The distance can be a few meters! The measuring cone has an opening angle of approximately 35 °. Applications are e.g.: Surface temperatures of windows, walls, ceilings for the detection of cold bridges, auto tires, the skin of burners and heaters, etc. This handy device is only 6.5 x3, 5x2cm in size, has a hold and lock function and a memory for min / max temperature.		23,50
2035%	TFA- Mini-Thermo-/Hygrometer Indoor temperature -10 to 60 °, Humidity: 10 - 99% RH Dimensions 53 x 39 x 15 mm		12,50

Filter mats for CVSrobusto set à 10 pieces dimensions 120x90mm category G3	8,00	9,52
Filter mats for CVSrobusto set à 10 pieces dimensions 120x90mm category G4	9,00	10,71
Filter mats for CVSrobusto set à 10 pieces dimensions 120x90mm category F5	11,00	13,09
Filter mats for CVSrobusto set à 10 pieces dimensions 120x90mm category F7	12,50	14,88